Jameco Part number 159353

External / Desktop Switching Power Supply

17W AC-DC Triple Output Desktop

- Full range AC input
- Soft start AC input<30A peak
- High reliability, low ripple, noise
- Compact size, light weight
- Short circuit protection
- OVP, OCP, OTP protection
- 100% full load burn-in test
- Fully enclosed plastic case
- Approvals: NRTLC/CSA/TUV/CE
- ISO-9002 certified manufacturer

106×66×38 mm

AC input range.....90~264VAC/ 0.7A
Setup, hold up time.....800ms, 18ms@full load, nominal line
Overload protection.....pulsing mode, auto recovery
Over voltage protection.....110%~140%
Operating temperature.....0-40℃@100% load
Withstand voltage.....I/P-O/P:3KVAC, I/P-FG:1.5KVAC, 1min.
Safety standards.....UL 1950, CSA 22.2, TUV EN60950
EMC standards.....EN55022, IEC801-2,3,4
Humidity.....20%~90%RH
Length of output cable.....150cm (typical)
Plug of DC output.....DIN 5 pin

Pin Assignment	
	PIN1: COM PIN2: GND PIN3: +5VDC PIN4: -Vout PIN5: +Vout

Stock No	Type No	Output	Tol.	R&N	Eff.	P.P.
13301	KA-60A	+5V, 0.1-1.0A	5%	50mV	70%	51
		+12V, 0.1-0.5A	5%	100mV		
		-12V, 0.1-0.5A	5%	100mV		
13302	KA-60B	+5V, 0.1-1.0A	5%	50mV	70%	51
		+15V, 0.1-0.4A	5%	100mV		
		-15V, 0.1-0.4A	5%	100mV		